HYSTER REACTION [RTLS]

AVAILABLE WITH PD AND CD SYSTEMS

Hyster Reaction™ is an industry-first technology package that helps reinforce lift truck operating best practices, tailored to the complexity of demanding, fast-paced indoor lift truck environments.

Real-Time Location Sensing (RTLS) utilizes ultra-wideband (UWB) technology to provide device-to-server connections, allowing custom truck performance rules when operating in specific areas of the facility. RTLS is available to pair with Proximity Detection (PD) or Collective Detection (CD) to create a robust operator assistance package. As always, Advanced Dynamic Stability (ADS) is standard with every package.

The system is governed at a maximum speed of 5 mph; when the system is active, it will bring the vehicle to a controlled crawl speed of 1.5 mph. Utilizing speed requirements helps improve operator and pedestrian awareness while keeping the operator in control of the lift truck.

BENEFICIAL USE CASES

Advanced Dynamic Stability
(traction & hydraulic controls)

- Adaptive speed controls
- Adaptive fork & load controls

Collision Avoidance Assist

- Truck-to-truck assist 360° field of view (CD/PD)
- Truck-to-object assist within path of travel, forks trailing (CD)
- Truck-to-pedestrian assist 360° field of view (CD/PD)
- Truck-to-beacon assist 360° field of view (CD/PD)

Location-Based Assist

- Exclusion zones
- End-of-aisle slowdown
- Exception zones
- Fork height restrictions
- Speed control zones

Hyster Tracker™ Wireless Monitoring (Level 1) is required when ordering Hyster Reaction.

VISIT US AT HYSTER.COM OR EMAIL REACTION@HYSTER.COM TO LEARN MORE.

©2025 Hyster-Yale Materials Handling, Inc. all rights reserved. Hyster and are trademarks of Hyster-Yale Materials Handling, Inc.
Hyster products are subject to change without notice.

0112HET4FC015_E_EN-US_V2R1_042025